

**CBS-2051e  
EXTRACTOR® Brewer Series**

Pulse-Brew Intermittent Spray Shower technology with programmable brew volume • brew time • bypass

- pre-wet percent • pre-wet delay • drip delay
- brew basket lock

Count on FETCO's leading-edge technology for superior performance. Our single 1.5 gallon EXTRACTOR® Series brewer is the perfect high volume solution when hot, fresh, aromatic coffee is needed. The CBS-2051e brews directly into the following 1.5 gallon dispensers: L3D-15, L3S-15, LS-15, TPD-15 and LD-15.

FETCO's commitment to developing ecology-friendly technology is top priority. FETCO® equipment does not contain mercury, lead or fiberglass. Instead, we use solid state relays, stainless steel fittings and insulation that does not contain harmful materials.



**CBS-2051e** with LUXUS® L3D-15 dispenser



E Series now comes standard with Cascading Spray Dome™.



**Water Specifications**

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	1.0	20-75

**Measurements**

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
37 1/4	12 3/4	20 3/8	55	64

**Standard Electrical Configurations**

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour (1)	
							cold water	hot water
E51016	2x3.0 KW	120/208	1	3+G	4.6	22.1	7.7	11.0
		120/220			5.1	23.4	8.9	11.0
		120/240			6.1	25.5	10.3	11.0
*E51026	2x3.0 KW	220/240	1	2+G	5.1-6.1	23.4-25.8	10.3	11.0

\*EXPORT ONLY

Specifications subject to change without notice.

(1) Based on standard factory settings:  
4.0 minute brew time: 0% pre-wet: 200° Water

